



PANASONIC

Panasonic 3312FLW TVK mounting base with push-in terminals and E+/E- connection

Product code 50025 · Emergency lighting > Field devices

White analogue mounting base for Panasonic addressable detectors and for MX emergency luminaires and exit signs. Push-in terminals for the COM loop and the E+/E- connection.

- Mounting base for MX emergency luminaires, exit signs and analogue detectors
- Push-in terminals for the COM loop and the E+/E- terminal pair
- Cable entry from above or from the side
- Recess for an address label holder
- Ceiling mounting, or wall mounting with MX luminaires



Product description

Panasonic 3312FLW is a white analogue mounting base that is connected to the COM loop. Panasonic analogue heat, smoke and multi-sensor detectors (types 33xx, 43xx and 44xx) as well as MX series emergency luminaires and exit signs can be installed in the base. The base is intended for dry indoor premises.

The base has push-in terminals (blue connector) for the COM loop in and out and a second pair of push-in terminals (grey connector, E+ and E-), to which an external indicator, for example 2218, is connected when the base is used with a detector. Cables can be brought into the base from above or from the side. The base has a recess for address label holder 3390, so the zone address or technical number can be read even when the detector is in place.

MX emergency luminaires

MX25, MX40 and MX Light luminaires are installed in base 3312FLW (or 3312W). In this case, both the COM loop and the emergency lighting supply line are connected to the base, and the luminaire is locked to the base with a hexagon socket screw. With MX luminaires, the base can be mounted on the ceiling or on the wall.

Installation

When used with a detector, the base is mounted on the ceiling. Screws are not included. The conductor size for the push-in terminals is 0.28–1.2 mm². Protective cover 3313 is available for the base.

Technical data

Product code	50025
Manufacturer	Panasonic
Product group	Emergency lighting > Field devices

Dimensions	Ø 102 × 15 mm
Operating temperature	-10...+50 °C
Storage temperature	-20...+70 °C
Humidity	Max. 95% RH, non-condensing
IP rating	IP51
Colour	White (Munsell 10Y9/0.5)
Material	ABS
Operating voltage	12–30 V DC (nominal 24 V DC)
Current consumption (quiescent)	0 mA
Mounting	Ceiling mounting (wall mounting also possible with MX luminaires)
Weight	47 g
Connection	Push-in terminals: COM loop (blue), external indicator E+/E- (grey); conductor 0.28–1.2 mm ²
Compatibility	Analogue detectors 33xx/43xx/44xx; MX emergency and exit luminaires
Standards	EN 61000-6-3, EN 50130-4

Documents

The manufacturer's original documents can be downloaded from the product page (QR code at the top of this sheet).

Technical datasheet: Panasonic 3312FLW TVK mounting base with push-in terminals

Product brochure: Panasonic 3312FLW TVK mounting base with push-in terminals

Technical datasheet (series): MX25, MX40 and MX Light

Request a quote or ask for more information

Sales +358 40 668 7641 · myynti@pap.fi · Mon–Fri 8 am – 4 pm (Finnish time)

Up-to-date information and documents: pap.fi/en/tuote/panasonic-3312flw-tvk-asennuskanta-pikaliittimill/