



## PANASONIC

# Panasonic 3379W addressable base sounder

Product code 41410 · Fire alarm systems > Field devices > Alarm devices

Addressable base sounder that combines an analogue detector base and a sounder. Brings the alarm sound into the same room as the detector without a separate sounder.

- Connected directly to the COM loop
- Three priority levels, each with its own tone type
- Sound level 86 dB(A), frequency 3,650 Hz
- Connection for an external indicator, e.g. 2218
- Approved to EN 54-3, CPR 0786-CPR-20954
- Can also be used without a detector with the 3313 protective cover



## Product description

Panasonic 3379W is a white addressable base sounder consisting of an analogue mounting base combined with a sounder. A Panasonic analogue detector is installed in the base, so the alarm sound is provided in the same room as the detector. The product is intended for dry indoor areas and is suitable for EBL512 G3 and EBL128 systems.

The base sounder has three priority levels (high, medium and low), each programmed in EBLWin with its own control expression and tone type. For example, a fire alarm elsewhere in the building can give one tone, an alarm on the same floor another, and an alarm from the base's own detector a third. A higher-priority condition changes the tone automatically. The options are a continuous tone, a 1 Hz intermittent tone and a 3 Hz intermittent tone.

One external indicator, for example the 2218 remote indicator, can be connected to the base via screw terminals E+ and E-.

## Installation

- Ceiling mounting, fixing screws not included
- The address (001–253) and operating mode are set with the 4414 address setting tool before connecting to the loop
- The detector in the base must have a different address from the base sounder
- Without a detector, the base is protected with the 3313 cover
- Conductor size Ø 0.6–1.2 mm (0.28–1.13 mm<sup>2</sup>)

## Technical data

|               |                                                    |
|---------------|----------------------------------------------------|
| Product code  | 41410                                              |
| Manufacturer  | Panasonic                                          |
| Product group | Fire alarm systems > Field devices > Alarm devices |

|                                 |                                                  |
|---------------------------------|--------------------------------------------------|
| Colour                          | White (Munsell 10Y9/0.5)                         |
| Weight                          | 80 g                                             |
| Dimensions                      | 160 × 102 × 25 mm                                |
| Sound output                    | 86 dB(A)                                         |
| Operating temperature           | -10...+50 °C                                     |
| EN 54 approval                  | EN 54-3                                          |
| CPR                             | 0786-CPR-20954                                   |
| Storage temperature             | -20...+70 °C                                     |
| Humidity                        | Max. 95% RH, non-condensing                      |
| Material                        | Flame-retardant ABS and polycarbonate            |
| IP rating                       | IP21                                             |
| Operating voltage               | 12–28 V DC (nominal 24 V DC)                     |
| Current consumption (quiescent) | ≤ 0.75 mA                                        |
| Current consumption (alarm)     | 2.5 ± 0.5 mA                                     |
| Frequency range                 | 3,650 ± 350 Hz                                   |
| Tone types                      | Continuous, intermittent 1 Hz, intermittent 3 Hz |
| Address range                   | 001–253                                          |
| Short-circuit isolator          | No                                               |
| Mounting                        | Ceiling mounting, dry indoor areas               |
| Standards                       | EN 61000-6-3, EN 50130-4, EN IEC 63000 (RoHS)    |

## Documents

The manufacturer's original documents can be downloaded from the product page (QR code at the top of this sheet).

**Technical datasheet:** 3379W addressable base sounder

**Certificate:** EU declaration of conformity, no. ESSC-F00016-09

**Certificate:** CPR certificate of constancy of performance, no. 0786-CPR-20954

**Certificate:** Declaration of performance (DoP), no. ESSC-FP0016-07 (Document No. 0786-CPD-20954 in the document)

### Request a quote or ask for more information

Sales +358 40 668 7641 · [myynti@pap.fi](mailto:myynti@pap.fi) · Mon–Fri 8 am – 4 pm (Finnish time)

Up-to-date information and documents: [pap.fi/en/tuote/panasonic-3379w-kantaaani-osoitteellinen-valkoinen/](https://pap.fi/en/tuote/panasonic-3379w-kantaaani-osoitteellinen-valkoinen/)