



## PANASONIC

# Panasonic ELOCLEAN automatic pipe cleaner

Product code 60115 · Aspirating smoke detection > Filters and maintenance

Automatically blows the Aspect detector's pipes clean 1–7 times a week. Intended for areas where dust settles in the pipes. 230 V AC, IP44.

- > Cleaning 1–7 times a week, also manual start
- > Fan 5,600 Pa (deliveries after 9/2022)
- > The detector is protected by an external valve during cleaning
- > IP44, –30...+60 °C



## Product description

ELOCLEAN is Panasonic's automatic pipe cleaner for the Aspect aspirating smoke detector. A powerful fan blows the dust out of the pipes. Cleaning starts automatically 1–7 times a week, and it can also be started manually or via an input. Before blowing, the external valve between the detector and ELOCLEAN is closed, and cleaning proceeds only once the valve is confirmed closed. Area 1 is cleaned first, then area 2; the whole procedure takes about three minutes.

According to Panasonic, ELOCLEAN is intended for extremely dusty sites where dust can be seen accumulating in the pipes or sampling holes, for example poultry houses and waste paper plants. The delivery includes the ELOCLEAN unit, a THUB 2-6 console with end caps, two external ball valves, four threaded pipe stubs, two extended T-joints and a 9 V lithium battery. Conduits for cables are not included.

## Technical data

|                     |                                                      |
|---------------------|------------------------------------------------------|
| Product code        | 60115                                                |
| Manufacturer        | Panasonic                                            |
| Manufacturer's code | ELOCLEAN                                             |
| Product group       | Aspirating smoke detection > Filters and maintenance |
| Operating voltage   | 230 V AC, 50 Hz                                      |
| Current consumption | Cleaning 2 A, standby 31 mA                          |
| Outputs             | Fault relay NC, 2 A / 30 V DC                        |
| Pressure            | 5,600 Pa                                             |

|                       |                                                      |
|-----------------------|------------------------------------------------------|
| Battery               | 9 V Li-SOCl <sub>2</sub> (tracks cleaning intervals) |
| IP rating             | IP44                                                 |
| Operating temperature | -30...+60 °C                                         |
| Humidity              | Max. 98%                                             |
| Dimensions            | 272 × 578 × 178 mm (W × H × D)                       |
| Weight                | 10.2 kg                                              |
| Compatibility         | Aspect AE2010                                        |

## Documents

The manufacturer's original documents can be downloaded from the product page (QR code at the top of this sheet).

**Datasheet:** ELOCLEAN

**Technical datasheet (series):** Aspect AE2010

**Product catalogue (series):** Aspect AE2010 accessories

### Request a quote or ask for more information

Sales +358 40 668 7641 · [myynti@pap.fi](mailto:myynti@pap.fi) · Mon–Fri 8 am – 4 pm (Finnish time)

Up-to-date information and documents: [pap.fi/en/tuote/panasonic-eloclean/](http://pap.fi/en/tuote/panasonic-eloclean/)