



SECURITON

Securiton TU 25 ABSRED sampling pipe Ø 25 mm, ABS, red, 3 m

Product code 61361 · Aspirating smoke detection > Pipes and installation accessories

Red ABS sampling pipe, outer diameter 25 mm, length 3 m. The pipe is marked "FIRE ALARM AIR SAMPLING PIPE DO NOT CUT OR PAINT".

- Sampling pipe system Ø 25 mm, red ABS
- Operating temperature -30...+60 °C (Securiton catalogue)
- Securiton's VdS-approved pipe material for ASD detectors



Product description

TU 25 ABSRED is Securiton's red ABS sampling pipe for aspirating smoke detector pipe networks. The outer diameter is 25 mm and the length 3 m. The pipe is marked "FIRE ALARM AIR SAMPLING PIPE DO NOT CUT OR PAINT". According to the pipe manufacturer's datasheet, the pipe must not be bent or painted, and the clip spacing at 20 °C is no more than 1.0 m.

According to Securiton's catalogue, the sampling pipe materials are part of the detector's VdS approval, so the pipe network is built from parts approved and listed by Securiton. The ABS parts are red with an outer diameter of 25 mm and are bonded with Glue 250 ABS. The operating temperature of the ABS pipe system is -30...+60 °C.

Technical data

Product code	61361
Manufacturer	Securiton
Manufacturer's code	TU 25 ABSRED (11-2300049-01-01)
Product group	Aspirating smoke detection > Pipes and installation accessories
Diameter	25 mm (outer)
Material	ABS
Colour	Red
Operating temperature	-30...+60 °C
Length	3 m
Marking	"FIRE ALARM AIR SAMPLING PIPE DO NOT CUT OR PAINT"
Compatibility	ASD 531, ASD 532, ASD 533, ASD 535, ASD 2000

Documents

The manufacturer's original documents can be downloaded from the product page (QR code at the top of this sheet).

Datasheet: TU 25 ABSRED

Product catalogue (series): sampling pipe materials ASD 531–535 (DE/EN)

Request a quote or ask for more information

Sales +358 40 668 7641 · myynti@pap.fi · Mon–Fri 8 am – 4 pm (Finnish time)

Up-to-date information and documents: pap.fi/en/tuote/securiton-tu-25-absred/