



Technical Data

	CRYPTO-BOX SC (CBUR2SC)	CRYPTO-BOX XS (CBUR2XS)	CRYPTO-BOX Versa (CBUR2VS)
Controller chip	Secure Microcontroller with USB interface		
Controller chip certification	EAL4+, WHQL (Microsoft)		
Firmware	Proprietary MARX		
Supported operating systems	Windows, Linux, macOS, iOS*, Android* (*network mode)		
AES/Rijndael 128 bit, implemented in hardware	✓ 8 keys (more on request)	✓ 3 keys	
RSA 2048 bit support, implemented in hardware	✓ 6 keys (more on request)	- (implemented on driver level, 1 key)	-
Unique Serial Number (BoxName) per device	✓	✓	- (same number per batch)
Network support	✓ (Floating License)	✓ (Floating License)	✓ (no license management)
Memory size (total)	72 kbyte, ca. 30 kbyte free	4, 32 or 64 kbyte	4kbyte
Internal memory read / write performance	read/write: approx. 80 kbyte/s	read/write: approx. 12 kbyte/s	
User-/admin password (PIN/PUK)	up to 16 byte length		
Case & LED	designer metal case, zinc cast, LED showing the operating state, eye for key ring		
Connector	USB Type A or USB Type C		
Memory programming	minimum 100.000 write cycles		
Data life cycle	minimum 10 years		
Conformity and certifications	CE and FCC, RoHS		
Measurements	USB-A: 32,5 x 14 x 7 mm / 1.28" x 0.55" x 0.28" USB-C: 22,5 x 11 x 4 mm / 0.89" x 0.43" x 0.16"		
Weight	USB-A: 7,5 g / 0.24 oz USB-C: 3 g / 0.11 oz		
Temperature range	-10°C to +70°C / 14°F to 158°F		
Air humidity	0% to 95% relative humidity		

MARX® Software Security GmbH

Vohburger Strasse 68
85104 Wackerstein, Germany

Phone: +49 (0) 8403 / 9295-0

contact-de@marx.com

MARX® CryptoTech LP

489 South Hill Street
Buford, GA 30518, U.S.A.

Phone: (+1) 770 904 0369

contact@marx.com

www.marx.com